Operation Guide 3079

CASIO.

About This Manual




- · Button operations are indicated using the letters shown
- in the illustration.

 Each section of this manual provides you with the information you need to perform operations in each mode. Further details and technical information can be found in the "Reference" section.

General Guide

- Press © to change from mode to mode.
 In any mode, press ① to illuminate the display.



Timekeeping



Use the Timekeeping Mode to set and view the current time and date.

Read This Before You Set the Time and Date!

The times displayed in the Timekeeping Mode and World Time Mode are linked. Because of this, make sure you select a city code for your Home City (the city where you normally use the watch) before you set the time and date.

To set the time and date



- 1. In the Timekeeping Mode, hold down (A) until the seconds start to flash, which indicates the setting
- screen.

 2. Press © to move the flashing in the sequence shown below to select other settings



3. When the setting you want to change is flashing, use \circledR and $ข{B}$ to change it as described below.

Screen	To do this:	Do this:
50	Reset the seconds to 00	Press D.
OFF	Toggle between Daylight Saving Time (CT) and Standard Time (CFF)	Press D.
TYO	Change the city code	Use (D) (east) and (B) (west).
° 10:58	Change the hour or minutes	Use (D) (+) and (B) (-).
154	Toggle between 12-hour (12H) and 24-hour (2HH) timekeeping	Press D.
2007	Change the year	Use () (+) and () (-).
6-30	Change the month or day	

- For full information on city codes, see the "City Code Table".

 See "Daylight Saving Time (DST)" for details about DST setting.

 Press (a) to exit the setting screen.

 With the 12-hour format, the P (PM) indicator appears on the display for times in the range of noon to 11:59 p.m. and no indicator appears for times in the range of midnight to 11:59 a.m.

 With the 24-hour format, times are displayed in the range of 0:00 to 23:59, without any indicator.

 The 12-hour/24-hour timekeeping format you select in the Timekeeping Mode is applied in all modes.

- applied in all modes.

 The day of the week is automatically displayed in accordance with the date (year, month, and day) settings

Daylight Saving Time (DST)

Daylight Saving Time (summer time) advances the time setting by one hour from Standard Time. Remember that not all countries or even local areas use Daylight Saving Time.

To toggle the Timekeeping Mode time between DST and Standard Time 1. In the Timekeeping Mode, hold down (a) until the seconds start to flash, which indicates the setting

1909 1:58

- screen.

 2. Press © to display the DST setting screen.


 3. Press © to toggle between Daylight Saving Time (Øf displayed) and Standard Time (Øf F displayed).

 Note that you cannot switch between Standard Time and Daylight Saving Time while GMT is selected as the Home City code.

 4. Press Ø, to exit the setting screen.

 The DST indicator appears on the display to indicate that Daylight Saving Time is turned on.

e-DATA MEMORY



You can use the watch's e-DATA MEMORY to store e-mail addresses, Web page URLs, and other text data. You can also use a password to limit access to e-DATA MEMORY contents.

All of the operations in this section are performed in the e-DATA MEMORY Mode, which you enter by pressing ©.

e-DATA MEMORY Management
e-DATA MEMORY can hold up to 315 characters total,
while each record can contain up to 63 characters. The
maximum number of records depends on the number of characters per record, as shown below.

- 63 characters per record: 5 records
 7 or fewer characters per record: 40 records



- To create a new e-DATA MEMORY record

 1. In the e-DATA MEMORY Mode, press ① and ③ at the same time to display the remaining memory stream.

 1. If the e-DATA MEMORY Mode, press ② and ③ at the same time to display the remaining memory is means that memory is full. To store another record, you will first have to delete some of the records stored in memory.

 2. Hold down ④ until the flashing cursor (圖) appears on the display, which indicates the setting screen.

 The setting screen also shows the record number that is automatically assigned to the new record.


 - 3. Input the text you want when inputting the text, use (i) (+) and (ii) (-) to cycle through characters at the current cursor location, and (iii) to move the cursor to the right. See "Inputting Text".



- 4. Press (A) to store your data and return to the e-DATA MEMORY record screen
- 4. Press (♠) to store your data and return to the e-DAIA MEMORY record screen (without the cursor).
 Pressing (♠) causes the message SET to appear for about two seconds as the data is stored. After that, the e-DAIA MEMORY record screen appears.
 The text can show only three characters at a time, so longer text scrolls continuously from right to left. The last character is indicated by the symbol 4 after it. Press (♠) to
- stop and restart scrolling.

 Records are stored in memory in the sequence they are created.

To recall e-DATA MEMORY records In the e-DATA MEMORY Mode, use 0 (+) and 8 (-) to cycle through e-DATA MEMORY records as shown below.









Remaining Memory Screen

Password Setting Screen

- The value on the remaining memory screen is the percentage of memory that is still
- available. It does not indicate the number of records that can be stored.

 The Password Setting screen shows - when a password is already registered.

 You can use the Password Setting screen to register, edit, or delete your password.

 See "Using a Password to Protect e-DATA MEMORY Data" for more information.

- **To edit an e-DATA MEMORY record** 1. In the e-DATA MEMORY Mode, use 0 (+) and 8 (-) to display the record you

- 1. If the 6-DATA MEMORY mode, use (i) (+) and (ii) (-) to display the record y want to edit.

 2. Hold down (ii) until the flashing cursor appears on the display.

 3. Use (ii) to move the flashing to the character you want to change.

 4. Use (iii) (+) and (iii) (-) to change the character.

 5. After making the changes you want, press (iii) to store them and return to the e-DATA MEMORY record screen.

- $\label{total conditions} \begin{tabular}{ll} \textbf{To delete an e-DATA MEMORY record} \\ 1. In the e-DATA MEMORY Mode, use \textcircled{D} (+) and \textcircled{B} (-) to display the record you are the condition of the condition of$ want to delete.

- want to delete.

 2. Hold down (a) until the flashing cursor appears on the display.

 3. Press (b) and (c) at the same time to delete the record.

 The message CLF appears to indicate that the record is being deleted. After the record is deleted, the cursor appears on the display, ready for input.

 4. Input data or press (a) to return to the remaining memory screen.

Using a Password to Protect e-DATA MEMORY Data

You can register a 4-digit password to keep e-DATA MEMORY data secure.

Use a 4-digit password that is easy for you to remember, but difficult for others to Use a 4-digit password that is easy for you to remember, social to the decipher. If you forget the password, you will have to have your watch initialized (which deletes all data in memory) in order to access the e-DATA MEMORY again. To have the watch initialized, contact the store or dealer where you purchased it, and ask



- 1. In the e-DATA MEMORY Mode, use ① (+) and ⑧ (-) to display the Password Setting screen.
- This displays a screen that shows SET PR5S.
 Hold down (A) for about one second until NEW appears, with the first (B flashing.)
 This is the New Password Setting screen.
- 3. Use ① (+) and ⑧ (-) to scroll through numbers at the first digit.
- 3. Use (b) (+) and (b) (-) to scoril through numbers at the first digit is the number you want, press (c) to advance to the next digit.

 5. Repeat steps 3 and 4 to input all four digits of the password you want.

 Pressing (a) while inputting a new password clears your input and returns to the Password Setting screen.

 6. After all four of the password digits are the way you want, press (c) to register

- them.

 Pressing © causes the message SET to appear for about one second as the password is stored. After that, the Password Setting screen appears.

 After registering a password, you can input, recall, edit and delete data, if you want. After you exit the e-DATA MEMORY Mode, you will have to input the password every time you want to enter it again.



- Enter the e-DATA MEMORY Mode.
 On the Password Input screen (---- PR55), press ① or ③. This causes the first digit of the password to flash.
- Inash.
 Input the password.
 Use (D) (+) and (B) (-) to scroll through numbers at
- each digit.

 Press © to advance to the next digit.

 Pressing & while inputting the password clears your input and returns to the Password Input screen.
- 4. After the password is the way you want, press ©.
 If the input password matches the one registered, the message OK! appears, followed by an e-DATA MEMORY screen.
 If the password does not match, the message ERR appears, followed by the
- Password Input screen.

- 1. Enter the e-DATA MEMORY Mode by inputting the current password.
 2. Use

 (+) and

 (-) to display the Password Setting screen.
 3. Perform the procedure starting from step 2 under "To register a new password" to specify the new password

- To delete the password

 1. Enter the e-DATA MEMORY Mode by inputting the current password.

 2. Use ⑤ (+) and ⑥ (-) to display the Password Setting screen.

 3. Hold down ⑥ for about one second until NEW appears, with the first ♂ flashing.

 4. Press ⑥ and ⑥ at the same time to delete the password.

 5. The message □LR appears to indicate that the password is being deleted. After the password is deleted, the Password Setting screen appears.

World Time



9:58

10:58 50

World Time shows the current time in 27 cities (29 time

All of the operations in this section are performed in the World Time Mode, which you enter by pressing ©.

To view the time in another city code In the World Time Mode, press ① to scroll through city codes (time zones) to the east or ③ to scroll to the west.

For full information about city codes, see the "City Code"

- If the current time shown for a city is wrong, check your Timekeeping Mode time and Home City code settings and make the necessary changes.

 When the currently selected time zone is one that includes mostly ocean, a value indicating the zone's Greenwich Mean Time differential appears in place of a city code.

- To toggle a city code time between Standard Time and Daylight Saving Time

 1. In the World Time Mode, use (a) and (b) to display the city code (time zone) whose Standard Time/Daylight Saving Time setting you want to change.

 2. Hold down (a) for about one second to toggle Daylight Saving Time (DST displayed) and Standard Time (DST opt displayed).

 - not displayed).

 The DST indicator is on the display whenever you display a city code for which Daylight Saving Time is turned on.
- Note that the DST/Standard Time setting affects only the currently displayed city code. Other city codes are not affected.
 Note that you cannot switch between Standard Time and Daylight Saving Time while
- GMT is selected as the city code.

Alarms



You can set up to five independent multi-function alarms with hour, minutes, month, and day. When an alarm is turned on, the alarm tone sounds when the alarm time is reached. One of the alarms is a snooze alarm, while the other four are one-time alarms. You can also input reminder text that appears when the alarm time is

reached.
You can also turn on an Hourly Time Signal that causes the watch to beep twice every hour on the hour.

There are five alarm screens numbered FiL 1 through

- AL4 for the one-time alarm, a snooze alarm screen indicated by \$1.5. The Hourly Time Signal screen is indicated by \$1.5. The Hourly Time Signal screen is indicated by \$1.5. In the case of the snooze alarm screen, the snooze alarm indicator (\$\pi\$) appears in the lower right corner of the display.
- · Alarm settings (and Hourly Time Signal settings) are available in the Alarm Mode, which you enter by pressing (C)

The alarm type is determined by the settings you make, as described below.

Set the hour and minutes for the alarm time. This type of setting causes the alarm to sound everyday at the time you set.

Date alarm

Set the month, day, hour and minutes for the alarm time. This type of setting causes the alarm to sound at the specific time, on the specific date you set.

Set the month, hour and minutes for the alarm time. This type of setting causes the alarm to sound everyday at the time you set, only during the month you set.

Monthly alarm Set the day, hour and minutes for the alarm time. This type of setting causes the alarm to sound every month at the time you set, on the day you set.



1. In the Alarm Mode, use (D) and (B) to scroll through the alarm screens until the one whose time you want to set is displayed.



- To set a one-time alarm, display one of the screens indicated by an alarm number from RL 1 through RL 4. To set the snooze alarm, display the screen indicated by SNZ.

 The snooze alarm repeats every five minutes.

 2. After you select an alarm, hold down ⑥ until the hour setting of the alarm time starts to flash, which indicates the setting screen.

 This operation automatically turns on the alarm.

 3. Press ⑥ to move the flashing in the sequence shown below to select other settings.



 Selecting the text causes the text input cursor (■) to appear. There are eight spaces in the text, so you have to press © eight times to move to the Hou

Operation Guide 3079

4. While a setting is flashing, use ①, ⑧, and ② to change it as described below

4. While a setting is hashing, use (a), (a), and (b) to change it as described below.								
Screen	To do this:	Do this:						
15:00	Change the hour and minutes	Use (h) (and (h) (-). • With the 12-hour format, set the time correctly as a.m. or p.m. (P indicator).						
	Change the month and day	To set an alarm that does not include a month and/or day, set - for each setting.						
Input reminder text		Use (+) and (-) to cycle through characters at the current cursor location, and (-) to move the cursor to the right. See "Inputting Text".						

Pressing (B) and (D) at the same time while any setting is flashing automatically sets the time to AM12:00 and the date to ----. It also clears any text that is inp for the alarm.



- 5. Press (A) to exit the setting screen.If you input reminder text, the text appears in place of the alarm number.
- If the reminder text is more than three characters, it will
- I the failline text is indeed in an under characters, it will scroll from right to left.

 If the alarm has a month and/or day setting, the month/ day appears at the bottom of the display, in place of the Timekeeping Mode time.

Alarm Operation



All of the graphic area segments start to flash, starting from the point the Timekeeping Mode time reaches one hour before an alarm time. This pre-alarm feature lets you know that an alarm time is about to be reached. The alarm tone sounds at the preset time for 10 seconds, regardless of the mode the watch is in. In the case of the snooze alarm, the alarm operation is performed a total of seven times, every five minutes, until you turn the alarm off.

- To stop the alarm tone after it starts to sound, press any button.
 The pre-alarm feature works in the Timekeeping Mode only. To stop the pre-alarm after it starts, press any button. Note, however, that pressing © also changes to the e-DATA MEMORY Mode.
- If you input reminder text for an alarm, the text appears for one minute on the Timekeeping Mode screen when the alarm time is reached. You can clear the reminder text display by pressing (A), (B), or (D), or by exiting the Timekeeping Mode.
- In the case of the snooze alarm, the reminder text appears on the Timekeeping
- Mode screen for the initial alarm operation only.

 Performing any one of the following operations during a 5-minute interval between snooze alarms cancels the current snooze alarm operation.

 Displaying the Timekeeping Mode setting screen

 Displaying the SHZ setting screen

 Changing the DST setting of the Home City code in the World Time Mode

To test the alarm In the Alarm Mode, hold down ① to sound the alarm.

To turn an alarm on and off



- orr

 1. In the Alarm Mode, use ① and ⑧ to select an alarm.

 2. Press ⑥ to toggle it on and off.

 Turning on a alarm (用L 1 to 用L 4, or SNZ) displays the alarm on indicator (☎) on its Alarm Mode screen.

 In all modes, the alarm on indicator is shown for any
- alarm that is currently turned on. The alarm on indicator flashes while the alarm is
- or the adaint of miscalar markes while the adaints sounding.

 The snooze alarm indicator (₺) flashes while the snooze alarm is sounding and during the 5-minute intervals between alarms.

To turn the Hourly Time Signal on and off 1. In the Alarm Mode, use and solution to select the Hourly



Time Signal (SIG).

2. Press (Â) to toggle it on (Br) and off (BFF).

The Hourly Time Signal on indicator (☼) is shown on the display in all modes while this function is turned on.

Hourly time signal on indicator

Countdown Timer



Timekeeping Mode time

- You can set the countdown timer within a range of one minute to 24 hours. An alarm sounds when the countdown reaches zero.

 • You can also select auto-repeat, which automatically
- restarts the countdown from the original value you set whenever zero is reached.
- The initial default countdown start time when you purchase the watch or after you have its battery replaced is 15 minutes. Countdown timer functions are available in the Countdown Timer Mode, which you can enter using ©.

To use the countdown timer

- Press

 while in the Countdown Timer Mode to start the countdown time
- . When the end of the countdown is reached and auto-repeat is turned off, the alarm
- sounds for 10 seconds or until you stop it by pressing any button. The countdown time is automatically reset to its starting value after the alarm stops.

 When the end of the countdown is reached and auto-repeat is turned on, the alarm sounds, but the countdown starts again automatically whenever the countdown
- The countdown timer measurement operation continues even if you exit the Countdown Timer Mode.
- Press (1) while a countdown operation is in progress to pause it. Press (1) again to
- To completely stop a countdown operation, first pause it (by pressing ①), and then press ③. This returns the countdown time to its starting value.




- To set up the countdown timer

 1. While the countdown start time is on the display in the Countdown Timer Mode, hold down (a) until the hour setting of the countdown start time starts to flash, which indicates the setting screen.

 If the countdown start time is not displayed, use the procedure "To use the countdown timer" to display it.

 2. Press (a) to move the flashing in the sequence shown below to select other settings.



3. While a setting is flashing, use (D) and (B) to change it as described below.

Screen	To do this:	Do this:		
0: 15	Change the hours or minutes	Use () (+) and () (-).		
OFF	Toggle auto-repeat on (CC) and off (CFF)	Press D.		

- To specify a countdown start time of 24 hours, set 3:30.

 4. Press (a) to exit the setting screen.

 The auto-repeat on indicator (x) appears on the display while this function is turned on.

 Frequent use of auto-repeat and the alarm can run down battery power.

Stopwatch



The stopwatch lets you measure elapsed time, split times, and two finishes.

- and two finishes.

 The display range of the stopwatch is 23 hours, 59 minutes, 59.99 seconds.

 The stopwatch continues to run, restarting from zero after it reaches its limit, until you stop it.

 The stopwatch measurement operation continues even if you exit the Stopwatch Mode.

 Exiting the Stopwatch Mode while a split time is frozen on the display clears the split time and returns to elapsed time measurement.
- All of the operations in this section are performed in the Stopwatch Mode, which you enter by pressing ©.

To measure times with the stopwatch



 The time on the screen may not appear to stop immediately when you press a button to stop timing or to perform a split operation. Despite this, the time recorded by your button operation is accurate.

Illumination



The display of the watch is illuminated by an LED (light rine uspialy or the watch is illuminated by an LED (light-emitting diode) and a light guide panel for easy reading in the dark. The watch's auto light switch turns on illumination automatically when you angle the watch towards your face for reading.

The auto light switch must be turned on (indicated by the auto light switch indicator) for it to operate.

See "Illumination Precautions" for more important information.


To illuminate the display manually In any mode, press ① to turn on illumination for about one second.

The above operation turns on illumination regardless of

About the Auto Light SwitchWhile the auto light switch is enabled, illumination turns on whenever you position your wrist as described below in any mode.

Moving the watch to a position that is parallel to the ground and then tilting it towards you at more than 40 degrees causes illumination to turn on.

• Wear the watch on the outside of your wrist.



- Warning!

 Always make sure you are in a safe place whenever you are reading the watch using the auto light switch. Be especially careful when running or engaged in any other activity that can result in accident or injury. Also take care that sudden illumination by the auto light switch does not startle or distract others around you.

 When you are wearing the watch, make sure that its auto light switch is turned off before riding on a bicycle or operating a motorcycle or any other motor vehicle. Sudden and unintended operation of the auto light switch can create a distraction, which can result in a traffic accident and serious personal injury.

Operation Guide 3079

CASIO

To turn the auto light switch on and off
In the Timekeeping Mode, hold down ℚ for about one second to toggle the auto light switch on (♣ displayed) or off (♣ not displayed).

• The auto light switch indicator is on the display in all modes while the auto light

- switch is turned on
- In order to protect against running down the battery, the auto light switch turns off automatically approximately six hours after you turn it on. Repeat the above procedure to turn the auto light switch back on if you want.

Reference

This section contains more detailed and technical information about watch operation. It also contains important precautions and notes about the various features and functions of this watch.

Graphic Areas

The following describes the information indicated by the three graphic areas in each

- In the Timekeeping Mode, World Time Mode, and Alarm Mode, the graphic areas indicate the passage of each minute and second of the current time (Timekeeping Mode time

- Mode time).

 In the e-DATA MEMORY Mode, the graphic areas indicate the number at the flashing digit during password input.

 In the Countdown Timer Mode, the graphic areas indicate the passage of each minute and second of the countdown.

 In the Stopwatch Mode, the graphic areas indicate the passage of each second and 1/10 except of the alternations. 1/10 second of the elapsed time



Timekeeping Mode

e-DATA MEMORY Mode


Inputting Text



The following describes how to input text in the e-DATA MEMORY and Alarm Modes.

To input characters

1. When the cursor is on the display, use ① and ⑧ to cycle through the available letters, numbers and symbols, in the sequence shown below.



- 2. When the character you want is at the cursor position, press © to move the cursor
- 3. Repeat steps 1 and 2 to input the rest of the characters you want
- See the "Character List" for information about the characters you can input

Auto Return Features

- If you leave the watch in the e-DATA MEMORY or Alarm Mode for two or three minutes without performing any operation, it automatically changes to the
- Timekeeping Mode.

 If you leave a screen with flashing digits or a cursor on the display for two or three minutes without performing any operation, the watch automatically exits the setting screen. Except for password input, any settings you have made up to that point are saved automatically

Scrolling

The (B) and (D) buttons are used in various modes and setting screens to scroll through data on the display. In most cases, holding down these buttons during a scroll operation scrolls at high speed

When you enter the e-DATA MEMORY, World Time, or Alarm Mode, the data you were viewing when you last exited the mode appears first.

Timekeeping

- Resetting the seconds to gg while the current count is in the range of 30 to 59 causes the minutes to be increased by 1. In the range of 00 to 29, the seconds are
- reset to £6 without changing the minutes.

 The year can be set in the range of 2000 to 2039.

 The watch's built-in full automatic calendar makes allowances for different month lengths and leap years. Once you set the date, there should be no reason to change it except after you have the watch's battery replaced.

World Time

- The current time in all World Time Mode cities is calculated in accordance with the Greenwich Mean Time (GMT) differential for each city, based on the current Home City time setting in the Timekeeping Mode.

 The seconds count of the World Time is synchronized with the seconds count of the
- Timekeeping Mode.

 The GMT differential is the time difference of the time zone where the city is located from Greenwich Mean Time.

 GMT differential is calculated by this watch based on Universal Time Coordinated

Illumination Precautions

- Illumination may be hard to see when viewed under direct sunlight.
 Illumination turns off automatically whenever an alarm sounds.
 Frequent use of illumination runs down the battery.

Auto light switch precautions

 Avoid wearing the watch on the inside of your wrist. Doing so causes the auto light switch to operate when it is not needed, which shortens battery life. If you want to wear the watch on the inside of your wrist, turn off the auto light switch feature



- Illumination may not turn on if the face of the watch is more than 15 degrees above or below parallel. Make sure that the back of your hand is parallel to the ground.
 Illumination turns off in about one second, even if you
- keep the watch pointed towards your face.
- Static electricity or magnetic force can interfere with proper operation of the auto light switch. If illumination does not turn on, try moving the watch back to the starting position (parallel with the ground) and then till it back towards you again. If this does not work, drop your arm all the way down so it hangs at your side, and then bring it
- Under certain conditions, illumination may not turn on until about one second after you turn the face of the watch towards you. This does not necessarily indicate malfunction of the auto light switch.

 You may notice a very faint clicking sound coming from the watch when it is shaken back and forth. This sound is caused by mechanical operation of the auto light switch, and does not indicate a problem with the watch.

Character List

	T			-7%		5.1		,					
		a.i	@	2	0	N	N	A	Α	n	n	a.	а
•	^	707	~	1	1	0	0	⊞	В	0	0	ь	b
8	&	1	/	2	2	P	Р		С	p	р	C	С
: ::::	=	\sim	1	3	3	Θ:	Q		D	q.	q	d	d
+	+	?	?	4	4	R	R	E	Е	h	r	e	е
((#	#	5	5	S	S	F	F	S	s	f	f
))	!	!	6	6	T	Т	G	G	t	t	9	g
		%	%	7	7	U	U	Н	Н	u.	u	h	h
				8	8	V	٧	Ι		V	٧	á	İ
		:	:	9	9	W	W	J	_	100	W	j	j
		;	;	340	*	X	Х	K	К	00	Х	k	k
		3	,	*****	-	Υ	Υ	L	L	У	у	l l	I
	1	,				Z	Z	М	М	Z	Z	m	m

City Code Table

City Code	City	GMT Differential	Other major cities in same time zone		
-11		-11.0	Pago Pago		
HNL	Honolulu	-10.0	Papeete		
ANC	Anchorage	-09.0	Nome		
LAX	Los Angeles	-08.0	San Francisco, Las Vegas, Vancouver, Seattle/Tacoma, Dawson City		
DEN	Denver	-07.0	El Paso, Edmonton		
CHI	Chicago	-06.0	Houston, Dallas/Ft. Worth, New Orleans, Mexico City, Winnipeq		
NYC	New York	-05.0	Montreal, Detroit, Miami, Boston, Panama City, Havana, Lima, Bogota		
CCS	Caracas	-04.0	La Paz, Santiago, Pt. Of Spain		
RIO	Rio De Janeiro	-03.0	Sao Paulo, Buenos Aires, Brasilia, Montevideo		
-2		-02.0			
-1		-01.0	Praia		
GMT		+00.0	Dublin, Lisbon, Casablanca, Dakar, Abidjan		
LON	London	+00.0			
PAR	Paris +01.0		Milan, Rome, Madrid, Amsterdam, Algiers, Hamburg, Frankfurt, Vienna, Stockholm, Berlin		
JRS	Cairo Jerusalem	+02.0	Athens, Helsinki, Istanbul, Beirut, Damascus, Cape Town		
JED	Jeddah	+03.0	Kuwait, Riyadh, Aden, Addis Ababa, Nairobi, Moscow		
THR	Tehran	+03.5	Shiraz		
DXB	Dubai	+04.0	Abu Dhabi, Muscat		
KBL	Kabul	+04.5			
KHI	Karachi	+05.0	Male		
DEL	Delhi	+05.5	Mumbai, Kolkata, Colombo		
DAC	Dhaka	+06.0			
RGN	Yangon	+06.5			
BKK	Bangkok	+07.0	Jakarta, Phnom Penh, Hanoi, Vientiane		
HKG	Hong Kong	+08.0	Singapore, Kuala Lumpur, Beijing, Taipei, Manila, Perth, Ulaanbaatar		
TYO	Tokyo	+09.0	Seoul, Pyongyang		
ADL	Adelaide	+09.5	Darwin		
SYD	Sydney	+10.0	Melbourne, Guam, Rabaul		
NOU	Noumea	+11.0	Pt. Vila		
WLG	Wellington	+12.0	Christchurch, Nadi, Nauru Is.		